

SECTION I - IDENTIFICATION	HAZARD RATING 0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme	Health	2
		Flammability	3
		Reactivity	2
		Personal Protection	G

IDENTITY (As Used on Label) Ceryl-A-Bond MT

COMMON NAME Methyl Methacrylate Copolymer

SECTION II - PRODUCT COMPONENTS	CAS.#	OSHA PEL	ACGIH TLV
Methyl Methacrylate	80-62-6	100 ppm	100 ppm
HEMA-Phosphate	52628-03-2	N.E. ¹	N.E.

¹N.E. = None Established

Warning: This material is highly flammable. Direct contact can cause severe irritation to the eyes, skin and respiratory tract. Inhalation and skin contact can cause an allergic sensitization. Inhalation of high vapor concentrations can cause headache, nausea, drowsiness and unconsciousness.

T.S.C.A. Status - O.K. on all above components.

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point °F	212 (MMA)	Specific Gravity (H ₂ O = 1)	1.2
Vapor Pressure (mbar @20 degrees C)	47	Melting Point	N/A
Vapor Density (AIR = 1)	>1	Evaporation rate (Butyl Acetate = 1)	>1

Solubility in Water miscible

Appearance and Odor Brown mobile liquid with an acrid fruity odor

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	50 F	Flammable Limits	LEL	UEL
			2.12%	12.5 % (MMA)

Extinguishing Media Use water mist, CO₂, foam, dry powder or cover with sand

Special Firefighting Procedures

Evacuate enclosed and surrounding areas. If smoke and fumes cannot be avoided, use proximity suit and self-contained breathing apparatus. Use water spray to cool containers and disperse vapors. Keep spills away from sources of ignition. Unusual Fire and Explosion Hazards

Vapor is heavier than air and forms explosive mixture with air. Never use welding or cutting torch on or near containers or drums (even when empty). Product residue or vapor in drum or container can ignite explosively.

SECTION V - REACTIVITY DATA

Stability	Unstable	X	Conditions to Avoid
	Stable		Keep containers closed when not in use.

Incompatibility (Materials to Avoid) Reducing agents, Oxidizing agents, solid polymeric particles

Hazardous Decomposition or Byproducts Thermal decomposition may yield water, oxides of carbon, and acid fumes

Hazardous Polymerization	May Occur	X	Conditions to Avoid: High temperatures, oxygen-free atmospheres, or contaminated areas. Avoid contact with peroxides, azocompounds and redox systems.
	Will Not Occur		

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation? YES	Skin? YES	Ingestion? YES
Signs and Symptoms of Exposure	Irritation of skin.		
Health Hazards (Acute and Chronic)	ACUTE - Irritation of skin and dermatitis. CHRONIC - Inhalation and skin contact can lead to an allergic respiratory sensitization. Persons may experience rapid irritation of skin upon exposure. Persons with lung disorders or who are sensitized should not use this product.		
Carcinogenicity:	NTP? NO	IARC Monographs? NO	OSHA Regulated? NO

Medical Conditions Generally Aggravated by Exposure
Allergy, skin disorders.

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.
SKIN - PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists.
INHALATION - May cause burns to the respiratory tract. Move person to fresh area if effects occur. If needed, give oxygen or artificial respiration to improve breathing. Consult physician.
INGESTION - Expected to be slightly toxic by ingestion. May cause burns to the gastrointestinal tract. If swallowed, induce vomiting immediately as directed by a physician. Get medical attention immediately.
Never give liquids to an unconscious or convulsing person.

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type): Atmospheric levels should be maintained below the exposure limits listed in section II by using engineering controls. Provide adequate exhaust ventilation and/or NIOSH approved cartridge respirator.

Ventilation	Local Exhaust	If needed.	Special	None known.
	Mechanical	Adequate exhaust ventilation must exhaust AWAY from applicator.		
Protective Gloves	Natural rubber or Neoprene.		Eye Protection	Splash goggles or face shield.

Other Protective Clothing or Equipment:

Use rubber apron, face shield and appropriate clothing to prevent contact with skin. Launder contaminated clothing before reuse. Discard contaminated leather shoes and canvas sneakers. Protective skin creams help cleaning with soap and water, gloves must still be worn. An eye wash station or an adequate supply of clean water must be available at work area.

Work/Hygienic Practices Establish good personal hygiene and work practices. Wash hands and face before eating, drinking or smoking.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: Wear protective equipment to prevent exposure. Stop spill and dike with sand or earth to prevent spreading. Avoid ignition sources. Absorb with sand or other non-flammable absorbent material and transfer to approved DOT drum for recovery or disposal. CERCLA/SARA requires notification of the appropriate Federal, State and Local authorities of releases of hazardous or extremely hazardous quantities equal to or greater than the reportable quantities (RQs) 40 CFR 302.4 and 40 CFR 355. SARA Title 313 requires submission of annual reports of releases of toxic chemicals that appear in 40 CFR 372. Components present in this product at a level which could require reporting are listed in section XII

Waste Disposal Method: This material is a hazardous waste (as per RCRA) because of its ignitability. Disposal should be conducted by an EPA or (RCRA) permitted Facility. CERCLA Reporting: Methyl Methacrylate (MMA) RQ=1000# SARA Title 313 reporting MMA

Precautions to be Taken in Handling and Storing:

Store in cool, dry, well-ventilated area away from sources of ignition. Keep containers tightly closed when not in use.

Other Precautions DO NOT THIN THIS PRODUCT

Prepared By: Bryan Ruck, Chemist

PLEASE NOTE

"The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."