



Material Safety Data Sheet

95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

Date Prepared 9/1/2008

SECTION I - IDENTIFICATION

IDENTITY (As Used on Label) **SL Filler Blend**

COMMON NAME Sand Aggregate

HAZARD RATING	Health	3
0 = Least	Flammability	0
1 = Slight	Reactivity	0
2 = Moderate	Personal Protection	F
3 = High		
4 = Extreme		

SECTION II - PRODUCT COMPONENTS

CAS.#	OSHA PEL	ACGIH TLV
Crystalline Silica (Quartz) ¹	14808-60-7	<u>10mg/m³</u> 0.05 mg/m ³
	%SiO ₂ +2	

¹Crystalline silica can be a lung injury and cancer hazard. Do not breathe dust. May cause delayed lung injury. Long term exposure can cause silicosis, a respiratory disease which can result in a delayed, disabling, and sometimes fatal lung injury.

Crystalline silica inhaled from occupational sources can from occupational sources can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure.

T.S.C.A. Status - O.K.

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	4046°F	Specific Gravity (H ₂ O = 1)	2.65
Vapor Pressure (mm Hg)	N/A	Melting Point	2930°F
Vapor Density (AIR = 1)	N/A	Evaporation rate (Butyl Acetate = 1)	N/A
Volatile Organic Compounds	0 g/L		
Solubility in Water	INSOLUBLE		
Appearance and Odor	Naturally rounded sand. Various sizes. No odor.		

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	N/A	Flammable Limits	LEL	UEL
			N/A	N/A

Extinguishing Media Compatible with all extinguishing media. Use any media appropriate for the surrounding fire.

Special Firefighting Procedures

N/A

Unusual Fire and Explosion Hazards

N/A

SECTION V - REACTIVITY DATA

Stability	Unstable	Conditions to Avoid
	Stable	NONE KNOWN.

Incompatibility (Materials to Avoid) Reducing agents, strong oxidizers, acids, alkalis, and accelerators

Hazardous Decomposition or Byproducts NONE KNOWN.

Hazardous Polymerization	May Occur	Conditions to Avoid
	Will Not Occur	NONE KNOWN.

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Yes	NO	NO

Signs and Symptoms of Exposure Shortness of breath and reduced pulmonary function.

Health Hazards (Acute and Chronic)

ACUTE - NO SYMPTOMS.

CHRONIC - excessive inhalation of dust may result in respiratory disease such as silicosis, pulmonary fibrosis, etc. The IARC has evaluated in Vol.42 (monographs) that there is "sufficient evidence for the Carcinogenicity of crystalline silica dust to experimental animal" and "limited evidence" with respect to humans.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	Yes (Respirable Silica)	YES*Level 2A Grouping	NO

Medical Conditions Generally Aggravated by Exposure

Lung disorders and persons subject to eye irritation.

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

SKIN - PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists.

INHALATION - Move person to fresh area if effects occur. If needed, give oxygen or artificial respiration to improve breathing. Consult physician.

INGESTION - Expected to be slightly toxic by ingestion. If swallowed, induce vomiting immediately as directed by a physician.

Get medical attention immediately. Never give liquids to an unconscious or convulsing person.

OTHER HEALTH EFFECTS - Medical conditions which may be aggravated by exposure to this product include, conjunctivitis of the eye, dermatitis of the skin, asthma and respiratory diseases. Sensitization may occur by skin contact.

****NOTE**** persons with lung disorders or who are sensitized should not use this product

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type)

"Provide adequate exhaust ventilation; use a NIOSH - approved respirator if PELs/TLVs are exceeded."

Ventilation	Local Exhaust	To meet PEL requirements.	Special	None Known.
	Mechanical	Adequate to meet PEL requirements.		

Protective Gloves Recommended. Eye Protection Recommended

Other Protective Clothing or Equipment

Use adequate ventilation and dust collection. To minimize exposure, wear a respirator approved for silica dust when using, handling, storing or disposing of this product. Refer to the most recent standards of ANSI (Z88.2), OSHA (29 CFR 1910.134), MSHA (30 CFR Parts 56 and 57), and NIOSH Respirator Decision Logic. Maintain, clean and fit test respirators in accordance with OSHA regulations.

Work/Hygienic Practices Avoid creating and breathing dust.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled

Do not breathe dust. Do not rely on your sight to determine if dust is in the air. Silica may be in the air without a visible dust cloud. Avoid creation of respirable dust

Waste Disposal Method

Dispose waste material in a sanitary land fill or as regulated by local, state and federal regulations.

Precautions to be Taken in Handling and Storing

Avoid creation of respirable dust. Take precaution against bag breakage.

Other Precautions None Known.

Prepared by: Samet Dy - Urethane Chemist

PLEASE NOTE "The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."