



Material Safety Data Sheet

95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

Date Prepared 8/2/2010

SECTION I - IDENTIFICATION

IDENTITY (As Used on Label) **Dur-A-Glaze #5 Resin**

COMMON NAME Aspartic ester polymer

HAZARD RATING	Health	2
0 = Least	Flammability	1
1 = Slight	Reactivity	0
2 = Moderate	Personal Protection	B
3 = High		
4 = Extreme		

SECTION II - PRODUCT COMPONENTS

	CAS.#	OSHA PEL	ACGIH TLV
Aminofunctional Reactive Thinner	Proprietary ²	N.E. ¹	N.E.
Proprietary diluent	Proprietary	N.E.	N.E.

¹Not Established

²The manufacturer of the component states that they will provide additional information to a health professional in the event of a medical emergency.

T.S.C.A. Status - O.K. on all above components.

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	212F	Specific Gravity (H2O = 1)	>1
Vapor Pressure (mm Hg)	NE	Melting Point	NE
Vapor Density (AIR = 1)	NE	Evaporation rate (Butyl Acetate = 1)	<1
Volatile Organic Compounds (VOC)	0 g/L		
Solubility in Water	Insoluble		
Appearance and Odor	Amber liquid. Slight odor.		

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	>200F	Flammable Limits	LEL	UEL
			NE	NE

Extinguishing Media Water spray, Foam, CO2, Dry Chemicals.

Special Firefighting Procedures

Wear full protective equipment including self-contained breathing apparatus.

Unusual Fire and Explosion Hazards

None Reported

SECTION V - REACTIVITY DATA

Stability	Unstable		Conditions to Avoid
	Stable	X	Excess heating over long periods may degrade the resin.
Incompatibility (Materials to Avoid)	Oxidizing materials		
Hazardous Decomposition or Byproducts	By Fire - Carbon monoxide, Carbon dioxide, other aliphatic fragments.		
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	None known.

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	YES	YES	YES

Signs and Symptoms of Exposure Irritation of skin.

Health Hazards (Acute and Chronic)

ACUTE - Irritation of skin and dermatitis. Irritation to nasal passages, throat, dizziness and headaches.

CHRONIC - None reported for this product. Effects are expected to be similar to those listed for acute human health effects.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO

Medical Conditions Generally Aggravated by Exposure

None known

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

SKIN - PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists.

INHALATION - Move person to fresh air. If needed, give oxygen or artificial respiration to improve breathing. Consult physician.

INGESTION - Get medical attention immediately. Never give liquids to an unconscious or convulsing person. Do not induce vomiting.

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type)

Provide adequate exhaust ventilation; use a NIOSH approved respirator if PELs/TLVs are exceeded.

Ventilation	Local Exhaust	If needed.	Special	None known.
	Mechanical	Adequate exhaust ventilation must exhaust AWAY from applicator.		

Protective Gloves Impermeable gloves

Eye Protection Splash goggles or face shield.

Other Protective Clothing or Equipment

Use rubber apron, face shield and appropriate clothing to prevent contact with skin. Launder contaminated clothing before reuse. Protective skin creams help cleaning with soap and water, gloves must still be worn.

An eye wash station or an adequate supply of clean water must be available at work area.

Work/Hygienic Practices Enforce careful handling to prevent splashing. Wash thoroughly after use.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled

Wear protective equipment to prevent exposure. Stop spill and dike to prevent spreading. Cover spill with absorbent materials and collect into containers. Clean contaminated area with detergent and water or a steam cleaner for best results.

Waste Disposal Method

Dispose in accordance with Federal, State and Local requirements.

Precautions to be Taken in Handling and Storing

Keep containers tightly closed when not in use.

Other Precautions NONE KNOWN.

Prepared by Samet Dy - Urethane Chemist

PLEASE NOTE *The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use.*



Material Safety Data Sheet

95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

Date Prepared 8/2/2010

SECTION I - IDENTIFICATION

IDENTITY (As Used on Label) Poly-Crete Hardener: MD/SL, HF, and TF/WR

COMMON NAME Aromatic Isocyanate Blend

HAZARD RATING	Health	2
0 = Least	Flammability	1
1 = Slight	Reactivity	1
2 = Moderate	Personal Protection	G
3 = High		
4 = Extreme		

SECTION II - PRODUCT COMPONENTS

	CAS.#	OSHA PEL	ACGIH TLV
Polyisocyanate based on MDI	Trade Secret ¹	NE ²	NE
4,4-Diphenylmethane Diisocyanate	101-68-8	0.02 ppm	0.005 ppm

¹The manufacturer of the component states that they will provide additional information to a health professional in the event of a medical emergency.

²None Established

T.S.C.A. Status - O.K. on all above components.

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	392°F	Specific Gravity (H2O = 1)	1.24
Vapor Pressure (mm Hg)	<10-5 @77F	Melting Point	NE
Vapor Density (AIR = 1)	8.5	Evaporation rate (Butyl Acetate = 1)	NE
Volatile Organic Compounds	0 g/L		
Solubility in Water	Reacts slowly with water to liberate CO ₂ gas		
Appearance and Odor	Dark Amber liquid. Faint Aromatic odor.		

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	>400°F	Flammable Limits	LEL	UEL
			NA	NA

Extinguishing Media Dry Chemicals, CO₂, Universal Type Foam, Water Fog

Special Firefighting Procedures

Wear full protective equipment including self-contained breathing apparatus. Water spray may be useful in minimizing vapors and cooling containers exposed to heat and flame. Avoid spreading burning liquid with H₂O used for cooling purposes.

Unusual Fire and Explosion Hazards MDI vapors and other irritating, highly toxic gases may be generated by thermal decomposition or combustion. At temperatures greater than 400F, polymeric MDI can polymerize and decompose which can cause pressure build-up in containers. Explosive rupture is possible. Cold water can cool fire-exposed containers.

SECTION V - REACTIVITY DATA

Stability	Unstable		Conditions to Avoid
	Stable	X	Keep containers closed when not in use.
Incompatibility (Materials to Avoid) Water, amines, strong bases, alcohols. copper alloys and aluminum, zinc.			
Hazardous Decomposition or Byproducts Fire: Carbon monoxide, oxides of Nitrogen, traces of HCN, MDI vapors or aerosols.			
Hazardous Polymerization	May Occur	X	Conditions to Avoid Contact with moisture, other materials which react with isocyanates, or temperatures above 400 F may cause polymerization.
	Will Not Occur		

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Yes	YES	Yes

Signs and Symptoms of Exposure Irritation and redness of skin and eyes. Breathing difficulty.

Health Hazards (Acute and Chronic) ACUTE Inhalation-can cause nasal and respiratory irritation, dizziness, headache, nausea.

Also, runny nose, sore throat, coughing, chest discomfort and reduced lung function. CHRONIC Inhalation-isocyanate sensitization can develop which can persist for weeks or years. Overexposure can cause lung damage which may be permanent. ACUTE Skin-isocyanates react with skin protein and cause irritation. CHRONIC Skin-prolonged contact can cause reddening, swelling, scaling, rash, blistering and skin sensitization. ACUTE Eye-tearing, reddening, swelling if untreated, corneal damage can result.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO

Medical Conditions Generally Aggravated by Exposure

Respiratory disorders (asthma, bronchitis, emphysema, bronchial hyperactivity), skin allergies, eczema.

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

Skin - remove contaminate clothing. Clean affected area with mild soap and water. If irritation or redness develops, seek medical attention.

INHALATION - move person away from source of exposure and into fresh air. If person is not breathing, give artificial respiration and seek medical attention immediately. If breathing difficulty develops, give oxygen and seek medical attention immediately.

Ingestion-DO NOT INDUCE VOMITING. Give 1 to 2 cups of milk or water to drink. Do not give anything by mouth to an unconscious person.

****NOTE** PERSONS WITH LUNG DISORDERS OR WHO ARE SENSITIZED SHOULD NOT USE THIS PRODUCT.**

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type) Use NIOSH approved respirator as outlined in 30CFR 11 and 29CFR 1910.134

effective for solvent and diisocyanate vapors. Use SCBA or air-supplied respirators when TLV/PEL is exceeded.

Ventilation	Local Exhaust	Use in confined areas.	Special	Sensitized persons must not inhale vapors
	Mechanical	Must be sufficient to maintain area below established TLV/PEL.		

Protective Gloves Neoprene rubber gloves. Eye Protection Splash proof goggles.

Other Protective Clothing or Equipment

Use other protective equipment such as rubber aprons and a face shield if danger of splashing is possible.

Eye wash station or clear water must be readily available. ENFORCE GOOD HYGIENE PRACTICES. No smoking or open lights in work area. Exposure to liquid, vapors, mists or fumes must be minimized. Use air supplied respirators in enclosed areas and when PEL/TLV is higher than established level.

Work/Hygienic Practices Launder contaminated clothing before use. Dispose contaminated leather shoes

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment, including respiratory equipment during clean-up. Absorb isocyanates with sawdust or another absorbent, shovel into unsealed containers, transport to a well-ventilated area. Decontaminate floor area.

Waste Disposal Method

Incineration in accordance with local, state, and federal regulations.

Precautions to be Taken in Handling and Storing Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected. Do not breathe aerosols or vapors. This material can cause asthmatic sensitization upon single exposure.

Other Precautions Exposure to vapors of heated MDI can be extremely dangerous.

Prepared by Samet Dy - Urethane Chemist

PLEASE NOTE *The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use.*



95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

Material Safety Data Sheet

Date Prepared 8/2/2010

SECTION I - IDENTIFICATION

IDENTITY (As Used on Label) Poly-Crete Resin: MD/SL, HF, and TF/WR all colors

COMMON NAME POLYOL-PIGMENT BLEND

HAZARD RATING 0 = Least 1 = Slight 2 = Moderate 3 = major 4 = Extreme	Health	1
	Flammability	1
	Reactivity	0
	Personal Protection	B

SECTION II - PRODUCT COMPONENTS

CAS.#	OSHA PEL	ACGIH TLV
Water	7732-18-5	N.E. ¹ N.E.
Polyester-ether polyol Blend	Proprietary2	N.E. N.E.
Glycol Ester Blend	Proprietary	N.E. N.E.
Rutile Titanium Dioxide	13463-67-7	10mg/m ³ 10mg/m ³
Inorganic Iron Oxides	1309-37-1	10mg/m ³ 10mg/m ³
Carbon Black	1333-86-4	3.5mg/m ³ (dust) .5mg/m ³ (dust)

¹None Established.

²The manufacturer of the component states that they will provide additional information to a health professional in the event of a medical emergency.

T.S.C.A. Status - O.K. on all above components.

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	212°F	Specific Gravity (H2O = 1)	>1
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	>1	Evaporation rate (Butyl Acetate = 1)	<1
Volatile Organic Compounds	0 g/L		
Solubility in Water	Dispersable		
Appearance and Odor	Viscous Liquid. Color varies upon desired shade. Faint Aromatic Odor.		

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	540°F	Flammable Limits	LEL N / A	UEL N / A
Extinguishing Media	Foam, CO ₂ , dry chemical, water spray.			
Special Firefighting Procedures	Wear full protective equipment including self-contained breathing apparatus.			

Unusual Fire and Explosion Hazards

Combustion products may be toxic. Cool storage containers with water spray to prevent pressure build-up that may rupture the containers.

SECTION V - REACTIVITY DATA

Stability	Unstable		Conditions to Avoid
	Stable	X	None known
Incompatibility (Materials to Avoid)	Strong Oxidants.		
Hazardous Decomposition or Byproducts	Burning will produce toxic fumes.		
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	Avoid contact with strong oxidizing agent.

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	No	Yes	Yes

Signs and Symptoms of Exposure Irritation of skin..

Health Hazards (Acute and Chronic)

ACUTE - Irritation of skin and dermatitis.

CHRONIC - Repeated over-exposure may cause skin irritation, dermatitis and sensitization.

Sensitized persons may experience rapid irritation of skin upon exposure.

NOTE: Persons with lung disorders or who are sensitized should not use this product.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No

Medical Conditions Generally Aggravated by Exposure

Allergy, skin disorders.

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

SKIN - Promptly wash with soap and water. Do not wash with solvents. Seek medical advice if irritation develops or persists.

INHALATION - Not a likely route of entry. Although this product is not known to cause respiratory problems, if breathing is difficult remove to fresh air and provide oxygen

INGESTION - Get medical attention immediately. Never give liquids to an unconscious or convulsing person.

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type)

Provide adequate exhaust ventilation; use a NIOSH approved respirator if PELs/TLVs are exceeded.

Ventilation	Local Exhaust	If needed.	Special	None known.
	Mechanical	Adequate exhaust ventilation must exhaust away from applicator.		
Protective Gloves	Natural Rubber or Neoprene		Eye Protection	Splash goggles or face shield.

Other Protective Clothing or Equipment

Use rubber apron, face shield and appropriate, clothing to prevent contact with skin. Launder contaminated clothing before reuse. Discard contaminated leather shoes and canvas sneakers. Protective skin creams may help, but gloves must still be worn. Clean-up with soap and water. An eye wash station or an adequate supply of clean water must be available at work area.

Work/Hygienic Practices Enforce careful handling to prevent splashing. Wash thoroughly after use.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled

Wear protective equipment to prevent exposure. Stop spill and dike to prevent spreading. Cover spill with absorbent materials and collect into containers. Clean contaminated area with detergent and water or a steam cleaner for best results.

Waste Disposal Method:

Dispose in accordance with Federal, State and Local requirements.

Precautions to be Taken in Handling and Storing

Keep containers tightly closed when not in use.

Other Precautions None known.

Prepared by Samet Dy - Urethane Chemist

PLEASE *The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use.*

DUR-A-FLEX® Inc.

95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

**Material Safety
Data Sheet**

Date Prepared 8/2/2010

SECTION I - IDENTIFICATIONIDENTITY (As Used on Label) **Dur-A-Glaze #5 Hardener**

COMMON NAME Aliphatic Polyisocyanate

HAZARD RATING

0 = Least

1 = Slight

2 = Moderate

3 = High

4 = Extreme

Health

2

Flammability

1

Reactivity

1

Personal Protection

G

SECTION II - PRODUCT COMPONENTS

	CAS.#	OSHA PEL	ACGIH TLV
HDI based Polyisocyanate	Trade Secret ²	N.E. ¹	N.E.
Hexamethylene Diisocyanate	822-06-0	N.E.	0.005ppm

¹Not Established²The manufacturer of the component states that they will provide additional information to a health professional in the event of a medical emergency.

T.S.C.A. Status - O.K. on all above components.

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**

Boiling Point	N.E.	Specific Gravity (H2O = 1)	>1
Vapor Pressure (mm Hg)	1.8 x 10 ⁻⁵	Melting Point	N.E.
Vapor Density (AIR = 1)	N.E.	Evaporation rate (Butyl Acetate = 1)	N.E.
Volatile Organic Compounds (VOC)	0 g/L		
Solubility in Water	NOT SOLUBLE.		
Appearance and Odor	Clear viscous liquid. Slight Odor.		

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	>200°F	Flammable Limits	LEL	UEL
			N.E.	N.E.

Extinguishing Media Dry Chemicals, CO2, Universal Type Foam.

Special Firefighting Procedures

Wear full protective equipment including self-contained breathing apparatus. Waterspray may be useful in minimizing vapors and cooling containers exposed to heat and flame. Avoid spreading burning liquid with H2O used for cooling purposes.

Unusual Fire and Explosion Hazards

Closed container may explode when exposed to extreme heat, or burst when contaminated with water.

SECTION V - REACTIVITY DATA

Stability	Unstable		Conditions to Avoid
	Stable	x	Keep containers closed when not in use.

Incompatibility (Materials to Avoid) Water, amines, strong bases, alcohols, metals and surface active materials.

Hazardous Decomposition or Byproducts Fire may yield CO, CO2, oxides of nitrogen and traces of HCN, HDI.

Hazardous Polymerization	May Occur	x	Conditions to Avoid
	Will Not Occur		Keep containers closed when not in use.

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Yes	Yes	Yes

Signs and Symptoms of Exposure Irritation and redness of skin and eyes. Breathing difficulty.

Health Hazards (Acute and Chronic)

ACUTE - prolonged skin exposure can cause irritation, dermatitis. Inhalation of vapors can cause nasal and respiratory irritation, dizziness, headache, nausea.

CHRONIC - prolonged or repeated exposure to vapors may cause liver and kidney damage. Lung disorders may aggravated by exposure.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO

Medical Conditions Generally Aggravated by Exposure

Asthma and other respiratory disorders, skin allergies, eczema

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

Skin - remove contaminate clothing. Clean affected area with mild soap and water. If irritation or redness develops, seek medical attention.

INHALATION- move person away from source of exposure and into fresh air. If person is not breathing, give artificial respiration and seek medical attention immediately. If breathing difficulty develops, give oxygen and seek medical attention immediately.

****NOTE** PERSONS WITH LUNG DISORDERS OR WHO ARE SENSITIZED SHOULD NOT USE THIS PRODUCT.****SECTION VII - CONTROL MEASURES**

Respiratory Protection (Specify Type) Use NIOSH approved respirator as outlined in 30CFR11 and 29CFR 1910.134 effective for diisocyanate vapors. Use SCBA or air-supplied respirators when TLV/PEL is exceeded.

Ventilation	Local Exhaust	Use in confined areas.	Special	Explosion proof fans when needed.
	Mechanical	Must be sufficient to maintain area below established TLV/PEL.		

Protective Gloves Neoprene rubber gloves. Eye Protection Splash proof goggles.

Other Protective Clothing or Equipment

Use other protective equipment such as rubber aprons and a face shield if danger of splashing is possible.

Eye wash station or clear water must be readily available. ENFORCE GOOD HYGIENE PRACTICES.

Exposure to liquid, vapors, mists or fumes must be minimized. Use air supplied respirators in enclosed areas and when PEL/TLV is higher than established level.

Work/Hygienic Practices Launder contaminated clothing before use. Dispose contaminated leather shoes

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled

Shut off and eliminate all ignition sources. Keep people away. Add sand, earth or other absorbent to spill area. Ventilate confined spaces. Open windows and doors, minimize breathing vapors and skin contact. Keep spill out of sewers by diking.

Waste Disposal Method

Incineration in accordance with local, state, and federal regulations.

Precautions to be Taken in Handling and Storing

Keep containers tightly closed when not in use. DO NOT pressurize, cut, weld, solder, drill or grind the containers.

Other Precautions None Known.

Prepared by Samet Dy - Urethane Chemist

PLEASE NOTE "The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."



Material Safety Data Sheet

95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

Date Prepared 8/2/2010

SECTION I - IDENTIFICATION

IDENTITY (As Used on Label) Poly-Crete Aggregate: MD, TC, SL, HF, TF, and WR

COMMON NAME Sand/Cement Aggregate

HAZARD RATING	Health	3
0 = Least	Flammability	0
1 = Slight	Reactivity	0
2 = Moderate	Personal Protection	G
3 = High		
4 = Extreme		

SECTION II - PRODUCT COMPONENTS

CAS.#	OSHA PEL	ACGIH TLV
Crystalline Silica (Quartz) ¹	14808-60-7	10mg/m ³ 0.05 mg/m ³
		%SiO ₂ +2
Portland Cement	65997-15-1	10mg/m ³ 10mg/m ³
		Total Dust Total Dust
Calcium/Magnesium Hydroxide	39445-23-3	15mg/m ³ 10mg/m ³
		Total Dust Total Dust

¹Crystalline silica can be a lung injury and cancer hazard. Do not breathe dust. May cause delayed lung injury. Long term exposure can cause silicosis, a respiratory disease which can result in a delayed, disabling, and sometimes fatal lung injury. Crystalline silica inhaled from occupational sources can from occupational sources can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure.

T.S.C.A. Status - O.K.

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	4,000°F	Specific Gravity (H ₂ O = 1)	>1
Vapor Pressure (mm Hg)	N/A	Melting Point	3,000°F
Vapor Density (AIR = 1)	N/A	Evaporation rate (Butyl Acetate = 1)	N/A
Volatile Organic Compounds	0 g/L		
Solubility in Water	INSOLUBLE		
Appearance and Odor	Naturally rounded sand. Various sizes. No odor.		

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	N/A	Flammable Limits	LEL	UEL
			N/A	N/A
Extinguishing Media	N/A			
Special Firefighting Procedures				
N/A				
Unusual Fire and Explosion Hazards				
N/A				

SECTION V - REACTIVITY DATA

Stability	Unstable		Conditions to Avoid
	Stable	X	NONE KNOWN.
Incompatibility (Materials to Avoid)	Hydrofluoric Acid and powerful oxidizing agents.		
Hazardous Decomposition or Byproducts	NONE KNOWN.		
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NONE KNOWN.

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Yes	NO	NO
Signs and Symptoms of Exposure	Shortness of breath and reduced pulmonary function.		
Health Hazards (Acute and Chronic)	ACUTE - NO SYMPTOMS. CHRONIC - excessive inhalation of dust may result in respiratory disease such as silicosis, pulmonary fibrosis, etc. The IARC has evaluated in Vol.42 (monographs) that there is "sufficient evidence for the Carcinogenicity of crystalline silica dust to experimental animal" and "limited evidence" with respect to humans.		
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	Yes (Respirable Silica)	YES*Level 2A Grouping	NO
Medical Conditions Generally Aggravated by Exposure	Lung disorders and persons subject to eye irritation.		
Emergency and First Aid Procedures	EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary. SKIN - PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists. INHALATION - Move person to fresh area if effects occur. If needed, give oxygen or artificial respiration to improve breathing. Consult physician. INGESTION - Expected to be slightly toxic by ingestion. If swallowed, induce vomiting immediately as directed by a physician. Get medical attention immediately. Never give liquids to an unconscious or convulsing person. OTHER HEALTH EFFECTS - Medical conditions which may be aggravated by exposure to this product include, conjunctivitis of the eye, dermatitis of the skin, asthma and respiratory diseases. Sensitization may occur by skin contact. **NOTE** persons with lung disorders or who are sensitized should not use this product		

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type): Atmospheric levels should be maintained below the exposure limits listed in section II by using engineering controls. Provide adequate exhaust ventilation and/or NIOSH approved cartridge respirator.				
Ventilation	Local Exhaust	To meet PEL requirements.	Special	None Known.
	Mechanical	Adequate to meet PEL requirements.		
Protective Gloves	Recommended.		Eye Protection	Recommended
Other Protective Clothing or Equipment	Use adequate ventilation and dust collection. To minimize exposure, wear a respirator approved for silica dust when using, handling, storing or disposing of this product. Refer to the most recent standards of ANSI (Z88.2), OSHA (29 CFR 1910.134), MSHA (30 CFR Parts 56 and 57), and NIOSH Respirator Decision Logic. Maintain, clean and fit test respirators in accordance with OSHA regulations.			
Work/Hygienic Practices	Avoid creating and breathing dust.			
SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE				
Steps to be Taken in Case Material is Released or Spilled	Do not breathe dust. Do not rely on your sight to determine if dust is in the air. Silica may be in the air without a visible dust cloud. Avoid creation of respirable dust			
Waste Disposal Method	Dispose waste material in a sanitary land fill or as regulated by local, state and federal regulations.			
Precautions to be Taken in Handling and Storing	Avoid creation of respirable dust. Take precaution against bag breakage.			
Other Precautions	None Known.			
Prepared by	Samet Dy - Urethane Chemist			

PLEASE "The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."



Material Safety Data Sheet

95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

Date Prepared 8/2/2010

SECTION I - IDENTIFICATION

Dur-A-Glaze Novolac/Pigmented Resin and Dur-A-Gard Novolac Resin

COMMON NAME Clear and Pigmented (all colors) Novolac Resin

HAZARD RATING	Health	1
0 = Least	Flammability	1
1 = Slight	Reactivity	0
2 = Moderate	Personal Protection	G
3 = High		
4 = Extreme		

SECTION II - PRODUCT COMPONENTS

CAS.#	OSHA PEL	ACGIH TLV
Diglycidyl Ether Bisphenol A Epoxy Resin	25068-38-6	N.E. ¹ N.E.
Aliphatic Glycidyl Ether Diluent	68609-97-2	N.E. N.E.
Novolac Epoxy Resin	28064-14-4	N.E. N.E.
Titanium Dioxide	13463-67-7	15mg/m ³ 10mg/m ³
Calcium Carbonate	1317-65-3	15mg/m ³ 10mg/m ³
Aluminum Silicate	1332-58-7	15mg/m ³ 2mg/m ³
Barium Sulfate ²	7727-43-7	10mg/m ³ 10mg/m ³
Inorganic Iron Oxides	1309-37-1	15mg/m ³ 10mg/m ³
Chromium(III) Oxide Green(trivalent chromium) ³	1308-38-9	1mg/m ³ 0.5mg/m ³

¹Not Established

²Barium Sulfate is listed in SARA III, Part 372, Section 313.

³This product contains only 1-3ppm (0.0001%-0.0003%) leachable hexavalent chromium. Trivalent chromium is not specifically listed as a possible carcinogen. Only in Dark Green and Light Green pigmented systems.

T.S.C.A. Status - O.K. on all above components.

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	N/A	Specific Gravity (H2O = 1)	1.55
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation rate (Butyl Acetate = 1)	N/A
Volatile Organic Compounds (VOC)	0 g/L		
Solubility in Water	NONE		
Appearance and Odor	Pigmented viscous liquid. Mild characteristic odor.		

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	485°F	Flammable Limits	LEL UEL
			N/A N/A

Extinguishing Media Water spray, Foam, CO₂, Dry Chemicals.

Special Firefighting Procedures

Wear full protective equipment including self-contained breathing apparatus.

Unusual Fire and Explosion Hazards

Cool storage containers with water spray to prevent pressure build-up that may rupture the containers.

Combustion products may be toxic.

SECTION V - REACTIVITY DATA

Stability	Unstable		Conditions to Avoid
	Stable	X	Excess heating over long periods of time degrades the resin.
Incompatibility (Materials to Avoid)	Uncontrolled reaction with amines.		
Hazardous Decomposition or Byproducts	By Fire - Carbon monoxide, Carbon dioxide, Nitrogen oxides, Aldehydes.		
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	Uncontrolled reaction with amines.

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	YES	YES	YES

Signs and Symptoms of Exposure Irritation of skin.

Health Hazards (Acute and Chronic)

ACUTE - Irritation of skin and dermatitis.

CHRONIC - Repeated overexposure will cause severe skin irritation, dermatitis and sensitization. Sensitized persons may experience rapid irritation of skin upon exposure.

Persons with lung disorders or who are sensitized should not use this product.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO

Medical Conditions Generally Aggravated by Exposure

Allergy, skin disorders.

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

SKIN - PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists.

INHALATION - Move person to fresh air if effects occur. If needed, give oxygen or artificial respiration to improve breathing. Consult physician.

INGESTION - Get medical attention immediately. Never give liquids to an unconscious or convulsing person.

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type)

Provide adequate exhaust ventilation; use a NIOSH approved respirator if PELS/TLVS are exceeded.

Ventilation	Local Exhaust	If needed.	Special	None known.
	Mechanical	Adequate exhaust ventilation must exhaust AWAY from applicator.		

Protective Gloves Natural rubber or Neoprene. Eye Protection Splash goggles or face shield.

Other Protective Clothing or Equipment

Use rubber apron, face shield and appropriate clothing to prevent contact with skin. Launder contaminated clothing before reuse. Discard contaminated leather shoes and canvas sneakers. Protective skin creams help cleaning with soap and water, gloves must still be worn. An eye wash station or an adequate supply of clean water must be available at work area.

Work/Hygienic Practices Enforce careful handling to prevent splashing. Wash thoroughly after use.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled

Wear protective equipment to prevent exposure. Stop spill and dike to prevent spreading. Cover spill with absorbent materials and collect into containers. Clean contaminated area with detergent and water or a steam cleaner for best results.

Waste Disposal Method

Dispose in accordance with Federal, State and Local requirements.

Precautions to be Taken in Handling and Storing

Keep containers tightly closed when not in use.

Other Precautions NONE KNOWN.

Prepared by Samet Dy - Chemist

PLEASE NOTE "The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."



95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

Material Safety Data Sheet

Date Prepared 8/2/2010

SECTION I - IDENTIFICATION

IDENTITY (As Used on Label) **Novolac Hardener**COMMON NAME **Epoxy Hardener**

HAZARD RATING 0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme	Health	3
	Flammability	1
	Reactivity	0
	Personal Protection	G

SECTION II - PRODUCT COMPONENTS

	CAS.#	%	OSHA PEL	ACGIH TLV
Benzyl Alcohol	100-51-6		N.E. ¹	N.E.
3, Aminomethyl -3,5,5-Trimethyl	2855-13-2		N.E.	N.E.
1, 5 Pentanediamine, 2 Methyl	15520-10-2		N.E.	N.E.
N, Aminoethyl Piperazine	140-31-8		N.E.	N.E.
Diglycidyl Ether Bisphenol A Epoxy Resin	25085-99-8		N.E.	N.E.
Salicylic Acid	69-72-7		N.E.	N.E.

¹None Established

T.S.C.A. Status - O.K. on all above components.

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	485°F	Specific Gravity (H ₂ O = 1)	>1
Vapor Pressure (mm Hg)	0.02	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation rate (Butyl Acetate = 1)	N/A
Volatile Organic Compounds (VOC)	0 g/L		
Solubility in Water	Partially Soluble.		
Appearance and Odor	Pale yellow colored liquid. Amine odor.		

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	220°F	Flammable Limits	LEL	UEL
			N/A	N/A

Extinguishing Media **Dry chemicals, carbon dioxide, foam water spray.**

Special Firefighting Procedures

Firefighters should wear full emergency equipment with self-contained breathing apparatus. Irritating and/or toxic gases may be generated by fire.

Unusual Fire and Explosion Hazards

Cool fire-exposed containers with cold water spray to prevent pressure buildup that may rupture the container.

SECTION V - REACTIVITY DATA

Stability	Unstable		Conditions to Avoid
	Stable	X	Keep container closed when not in use.

Incompatibility (Materials to Avoid) **Strong oxidizers and acids.**Hazardous Decomposition or Byproducts **Fire- Carbon Monoxide, Carbon Dioxide, Nitrogen, Aldehydes.**

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	Uncontrolled reaction with epoxy resin. Avoid breathing fumes generated by hardener and epoxy mixture when not used in established pot life.

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	YES	YES	YES

Signs and Symptoms of Exposure **Irritation on skin, eyes or respiratory tract.**Health Hazards (Acute and Chronic) **Note: Persons with lung disorders or who are sensitized should not use this product**

ACUTE - prolonged skin exposure can cause irritation, dermatitis. Inhalation of vapors can cause nasal and respiratory irritation, dizziness, headache, nausea.

CHRONIC - prolonged or repeated exposure to vapors may cause liver and kidney damage. Lung disorders may be aggravated by exposure.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO

Medical Conditions Generally Aggravated by Exposure

Allergy, eczema, skin conditions, and lung disorders.

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

SKIN - PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists.

INHALATION - Move person to fresh air if effects occur. If needed, give oxygen or artificial respiration to improve breathing. Consult physician.

INGESTION - Get medical attention immediately. Never give liquids to an unconscious or convulsing person.

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type)

Provide adequate exhaust ventilation; use a NIOSH - approved respirator if PELS/TLVS are exceeded.

Ventilation	Local Exhaust	Use in confined areas.	Special	Explosion-proof fans when needed.
	Mechanical	Must be sufficient to maintain area below established TLV/PEL.		

Protective Gloves **Neoprene rubber gloves.** Eye Protective **Splash goggles or face shield.**

Other Protective Clothing or Equipment

Use other protective equipment such as rubber aprons and a faceshield if danger of splashing is possible.

Eye wash station or clear water must be readily available. ENFORCE GOOD HYGIENE PRACTICES. No smoking or open lights in work area. Exposure to liquid, vapors, mists or fumes must be minimized. Use air supplied respirators in enclosed areas and when PEL/TLV is higher than established level.

Work/Hygienic Practices **Laundry contaminated clothing before use. Dispose contaminated leather shoes or sneakers.**

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled

Shut off and eliminate all ignition sources. Keep people away. Add sand, earth or other absorbent to spill area.

Ventilate confined spaces. Open windows and doors, minimize breathing vapors and skin contact. Keep spill out of sewers by diking. Observe precautions for flammable vapors from absorbed materials.

Waste Disposal Method

Burn in an adequate incinerator or bury in an approved landfill in accordance with federal, state and local regulations.

Precautions to be Taken in Handling and Storing **Keep containers tightly closed when not in use and away from excessive heat and flame. Do not pressurize, cut, weld, solder, drill, or grind the containers.**Other Precautions **NONE KNOWN.**Prepared by **Samet Dy - Chemist**

PLEASE NOTE "The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."



Material Safety Data Sheet

95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

Date Prepared 8/2/2010

SECTION I - IDENTIFICATION

IDENTITY (As Used on Label) Dur-A-Chips/ Cryl-A-Chips

COMMON NAME Pigmented Vinyl Flakes

HAZARD RATING	Health	1
0 = Least	Flammability	0
1 = Slight	Reactivity	0
2 = Moderate	Personal Protection	A
3 = High		
4 = Extreme		

SECTION II - PRODUCT COMPONENTS

CAS.#	OSHA PEL	ACGIH TLV
Ethylene Glycol 107-21-1	NE ¹	50ppm

¹None Established

T.S.C.A. Status - O.K. on all components

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	N/A	Specific Gravity (H ₂ O = 1)	2.5
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation rate (Butyl Acetate = 1)	N/A

Volatile Organic Compounds (VOC) = Zero grams/liter

Solubility in Water Insoluble

Appearance and Odor Various colored flakes.

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	N/A	Flammable Limits	LEL	UEL
			N/A	N/A

Extinguishing Media Water or carbon dioxide

Special Firefighting Procedures

Use respiratory masks to remove smoke and organic vapors.

Unusual Fire and Explosion Hazards

When polymer burns, water, carbon dioxide, carbon monoxide and smoke are produced.

SECTION V - REACTIVITY DATA

Stability	Unstable	Conditions to Avoid
	Stable	X Sulfuric acid and alkali materials.

Incompatibility (Materials to Avoid) None known

Hazardous Decomposition or Byproducts Upon burning - acetic acid, acetaldehyde, carbon dioxide.

Hazardous Polymerization	May Occur	Conditions to Avoid
	Will Not Occur	X None known

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Yes	No	Possible

Signs and Symptoms of Exposure Bronchial irritation.

Health Hazards (Acute and Chronic)

No toxic effects have been noted from inhalation or ingestion in animals with exposure. Human health effects of overexposure may include a respiratory irritation with cough and shortness of breath. Individuals with pre-existing lung diseases may react more to over-exposure.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No

Medical Conditions Generally Aggravated by Exposure

May aggravate pre-existing respiratory conditions.

Emergency and First Aid Procedures

Wash dust from the skin with soap and water. Flush out eyes with generous amounts of water for at least 15 minutes. See a physician if necessary.

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type)

Provide adequate exhaust ventilation; use a NIOSH approved respirator if PELS/TLVS are exceeded.

Ventilation	Local Exhaust	Use when needed.	Special	None
	Mechanical	Not usually required.		

Protective Gloves Not usually required. Eye Protection Safety glasses.

Other Protective Clothing or Equipment

Use a dust mask in a dusty environment.

Work/Hygienic Practices Nothing unusual. Avoid dust.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled

Not a RCRA listed hazardous waste. Sweep up and/or shovel or use a vacuum to clean up spillage.

Deposit into covered container for disposal.

Waste Disposal Method

Dispose of according to Federal, State, or local regulations. If approved, remove to land disposal area.

Precautions to be Taken in Handling and Storing

In case of skin contact, the compound is not likely to be hazardous but cleaning the skin after use is advisable.

Other Precautions None known

Prepared by Samet Dy - Urethane Chemist

PLEASE NOTE "The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."