



# Material Safety Data Sheet

95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

Date Prepared 8/2/2010

## SECTION I - IDENTIFICATION

IDENTITY (As Used on Label) **Dur-A-Glaze #4 RESIN/ Bio-Pruf®**

COMMON NAME Epoxy Resin

HAZARD RATING	Health	1
0 = Least	Flammability	1
1 = Slight	Reactivity	0
2 = Moderate	Personal Protection	G
3 = High		
4 = Extreme		

## SECTION II - PRODUCT COMPONENTS

	CAS.#	OSHA PEL	ACGIH TLV
Diglycidyl Ether Bisphenol A Epoxy Resin	25085-99-8	N.E. <sup>1</sup>	N.E.
Aliphatic Glycidyl Ether Diluent	68609-97-2	N.E.	N.E.
Film Additives	Proprietary <sup>2</sup>	N.E.	N.E.

<sup>1</sup>Not Established

<sup>2</sup>The manufacturer of these component states that they will provide additional information to a health professional in the event of an emergency.

T.S.C.A. Status - O.K. on all above components.

**\*FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300\***

## SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	N/A	Specific Gravity (H2O = 1)	>1
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation rate (Butyl Acetate = 1)	N/A
Volatile Organic Compounds (VOC)	0 g/L		
Solubility in Water	None		
Appearance and Odor	Viscous liquid. Mild characteristic odor.		

## SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	485°F	Flammable Limits	LEL	UEL
			N/A	N/A

Extinguishing Media Foam, CO<sub>2</sub>, Dry Chemical, Water Spray.

Special Firefighting Procedures

Firefighters should wear full emergency equipment with self-contained breathing apparatus.

Unusual Fire and Explosion Hazards

Cool fire - exposed containers with cold water spray to prevent pressure build - up that may rupture the container. Combustion products may be toxic.

## SECTION V - REACTIVITY DATA

Stability	Unstable		Conditions to Avoid
	Stable	X	Excess heating over long periods of time degrades the resin.
Incompatibility (Materials to Avoid)	Uncontrolled reaction with amines.		
Hazardous Decomposition or Byproducts	Fire- Carbon Monoxide, Carbon Dioxide, Nitrogen Oxide, Aldehydes.		
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	Uncontrolled reaction with amines.

## SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	YES	YES	YES

Signs and Symptoms of Exposure Irritation on skin.

Health Hazards (Acute and Chronic)

ACUTE - Irritation on skin and dermatitis.

CHRONIC - Repeated overexposure will cause severe skin irritation, dermatitis and sensitization.

Sensitized persons may experience rapid irritation of skin upon exposure.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO

Medical Conditions Generally Aggravated by Exposure

Allergy, skin disorders.

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

SKIN - PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists.

INHALATION - Move person to fresh air if effects occur. If needed, give oxygen or artificial respiration to improve breathing. Consult physician.

INGESTION - Get medical attention immediately. Never give liquids to an unconscious or convulsing person.

Note: Persons with lung disorders or who are sensitized should not use this product.

## SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type)

Provide adequate exhaust ventilation; use a NIOSH - approved respirator if PELS/TLVS are exceeded.

Ventilation	Local Exhaust	If needed.	Special	None known.
	Mechanical	Adequate exhaust ventilation must exhaust AWAY from applicator.		

Protective Gloves Natural or Neoprene gloves. Eye Protector Splash goggles or face shield.

Other Protective Clothing or Equipment

Use rubber apron, face shield and appropriate clothing to prevent contact with skin. Launder contaminated clothing before reuse. Discard contaminated leather shoes and canvas sneakers. Protective skin creams help cleaning with soap and water, gloves must be still be worn. An eye wash station or an adequate supply of clean water must be available at work area.

Work/Hygienic Practices Enforce careful handling to prevent splashing. Wash thoroughly after use.

## SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled

Wear protective equipment to prevent exposure. Stop spill and dike to prevent spreading. Cover spill with absorbent materials and collect into containers. Clean contaminated area with detergent and water or a steam cleaner for best results.

Waste Disposal Method

Dispose in accordance with Federal, State, and Local requirements.

Precautions to be Taken in Handling and Storing

Keep containers tightly closed when not in use.

Other Precautions NONE KNOWN.

Prepared by Samet Dy - Chemist

**PLEASE NOTE** "The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."



# Material Safety Data Sheet

95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

Date Prepared 8/2/2010

## SECTION I - IDENTIFICATION

**IDENTITY (As Used on Label)** Dur-A-Glaze #4 Hardener: Regular, Fast, Cold Cure, CR4, Damp-Primer, Water Clear

**COMMON NAME** Epoxy Resin Curatives

HAZARD RATING 0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme	Health	3
	Flammability	1
	Reactivity	0
	Personal Protection	G

## SECTION II - PRODUCT COMPONENTS

	CAS.#	OSHA PEL	ACGIH TLV
Benzyl Alcohol	100-51-6	N.E. <sup>1</sup>	N.E.
3, Aminomethyl -3,5,5-Trimethyl	2855-13-2	N.E.	N.E.
1, 5 Pentanediamine, 2 Methyl	15520-10-2	N.E.	N.E.
N, Aminoethyl Piperazine	140-31-8	N.E.	N.E.
Diglycidyl Ether Bisphenol A Epoxy Resin	25085-99-8	N.E.	N.E.
Salicylic Acid	69-72-7	N.E.	N.E.
1, 5 Pentanediamine, 2 Methyl	15520-10-2	N.E.	N.E.
Benzene-1,3-Dimethaneamine	1477-550	N.E.	N.E.
Phenol	108-95-2	N.E.	N.E.
Triphenyl phosphite	101-02-0	N.E.	N.E.

<sup>1</sup>None Established

T.S.C.A. Status - O.K. on all above components.

**\*FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300\***

## SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	485°F	Specific Gravity (H <sub>2</sub> O = 1)	<1
Vapor Pressure (mm Hg)	0.02	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation rate (Butyl Acetate = 1)	N/A
Volatile Organic Compounds (VOC)	0 g/l		
Solubility in Water	Partially soluble.		
Appearance and Odor	Pale yellow colored liquid. Amine odor.		

## SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	220°F	Flammable Limits	LEL	UEL
			N/A	N/A
Extinguishing Media	Dry chemicals, carbon dioxide, foam, water spray.			
Special Firefighting Procedures				
Firefighters should wear full emergency equipment with self-contained breathing apparatus. Irritating gases may be generated by fire.				
Unusual Fire and Explosion Hazards				
Cool exposed containers with cold water spray to prevent pressure buildup that may rupture the containers.				

## SECTION V - REACTIVITY DATA

Stability	Unstable	Conditions to Avoid
	Stable	
Incompatibility (Materials to Avoid)	Strong oxidizers and acids.	
Hazardous Decomposition or Byproducts	By Fire- carbon monoxide, carbon dioxide, aldehydes, nitrogen.	
Hazardous Polymerization	May Occur	Conditions to Avoid
	Will Not Occur	

## SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	YES	YES	YES
Signs and Symptoms of Exposure	Irritation on skin.		
Health Hazards (Acute and Chronic)			
Note: Persons with lung disorders or who are sensitized should not use this product.			
ACUTE - Irritation on skin and dermatitis.			
CHRONIC - Repeated overexposure will cause severe skin irritation, dermatitis and sensitization. Sensitized persons may experience rapid irritation of skin upon exposure.			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO
Medical Conditions Generally Aggravated by Exposure	Allergy, skin disorders.		
Emergency and First Aid Procedures			
EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.			
SKIN - PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists.			
INHALATION - Move person to fresh air if effects occur. If needed, give oxygen or artificial respiration to improve breathing. Consult physician.			
INGESTION - Get medical attention immediately. Never give liquids to an unconscious or convulsing person.			

## SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type)			
Provide adequate exhaust ventilation; use a NIOSH approved respirator if PELs/TLVs are exceeded.			
Ventilation	Local Exhaust	If needed.	Special None known.
	Mechanical	Adequate exhaust ventilation must exhaust AWAY from applicator.	
Protective Gloves	Natural or Neoprene gloves.		Eye Protection Splash goggles or face shield.
Other Protective Clothing or Equipment			
Use rubber apron, face shield and appropriate clothing to prevent contact with skin. Launder contaminated clothing before reuse. Discard contaminated leather shoes and canvas sneakers. Protective skin creams help cleaning with soap and water, gloves must be still be worn. An eye wash station or an adequate supply of clean water must be available at work area.			
Work/Hygenic Practices Enforce careful handling to prevent splashing. Wash thoroughly after use.			

## SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled	
Wear protective equipment to prevent exposure. Stop spill and dike to prevent spreading. Cover spill with absorbent materials and collect into containers. Clean contaminated area with detergent and water or a steam cleaner for best results.	
Waste Disposal Method	
Dispose in accordance with Federal, State, and Local requirements.	
Precautions to be Taken in Handling and Storing	
Keep containers tightly closed when not in use.	
Other Precautions	NONE KNOWN.
Prepared by	Samet Dy - Chemist

**PLEASE NOTE** \*The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use.\*



95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

# Material Safety Data Sheet

Date Prepared 8/2/2010

## SECTION I - IDENTIFICATION

**IDENTITY (As Used on Label)** Shop Floor Resin: all colors

**COMMON NAME** Pigmented Epoxy Resin

HAZARD RATING	Health	1
0 = Least	Flammability	1
1 = Slight	Reactivity	0
2 = Moderate	Personal Protection	G
3 = High		
4 = Extreme		

## SECTION II - PRODUCT COMPONENTS

CAS.#	OSHA PEL	ACGIH TLV
Diglycidyl Ether Bisphenol A Epoxy Resin	25068-38-6	N.E. <sup>1</sup> N.E.
Aliphatic Glycidyl Ether Diluent	68609-97-2	N.E. N.E.
Titanium Dioxide	13463-67-7	15mg/m <sup>3</sup> 10mg/m <sup>3</sup>
Calcium Carbonate	1317-65-3	15mg/m <sup>3</sup> 10mg/m <sup>3</sup>
Aluminum Silicate	1332-58-7	15mg/m <sup>3</sup> 2mg/m <sup>3</sup>
Barium Sulfate <sup>2</sup>	7727-43-7	10mg/m <sup>3</sup> 10mg/m <sup>3</sup>
Inorganic Iron Oxides	1309-37-1	15mg/m <sup>3</sup> 10mg/m <sup>3</sup>
Chromium(III) Oxide Green(trivalent chromium) <sup>3</sup>	1308-38-9	1.0mg/m <sup>3</sup> 0.5mg/m <sup>3</sup>

<sup>1</sup>Not Established

<sup>2</sup>Barium Sulfate is listed in SARA III, Part 372, Section 313.

<sup>3</sup>This product contains only 1-3ppm (0.0001%-0.0003%) leachable hexavalent chromium. Trivalent chromium is not specifically listed as a possible carcinogen. Only in Dark Green and Light Green pigmented systems.

T.S.C.A. Status - O.K. on all above components.

**\*FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300\***

## SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	N/A	Specific Gravity (H2O = 1)	1.2
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation rate (Butyl Acetate = 1)	>1
Volatile Organic Compounds	0 g/L		
Solubility in Water	Not Soluble		
Appearance and Odor	Pigmented viscous liquid. Mild characteristic odor.		

## SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	485°F	Flammable Limits	LEL	UEL
			N/A	N/A

Extinguishing Media Water spray, Foam, CO<sub>2</sub>, Dry Chemicals.

Special Firefighting Procedures

Wear full protective equipment including self - contained breathing apparatus.

Unusual Fire and Explosion Hazards

Cool storage containers with water spray to prevent pressure build-up that may rupture the containers.

Combustion products may be toxic.

## SECTION V - REACTIVITY DATA

Stability	Unstable	Conditions to Avoid
	Stable	X Excess heating over long periods of time degrades the resin.

Incompatibility (Materials to Avoid) Uncontrolled reaction with amines.

Hazardous Decomposition or Byproducts By Fire - Carbon monoxide, Carbon dioxide, Nitrogen oxides, Aldehydes.

Hazardous Polymerization	May Occur	Conditions to Avoid
	Will Not Occur	X Uncontrolled reaction with amines.

## SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	YES	YES	YES

Signs and Symptoms of Exposure Irritation of skin.

Health Hazards (Acute and Chronic)

ACUTE - Irritation of skin and dermatitis.

CHRONIC - Repeated overexposure will cause severe skin irritation, dermatitis and sensitization. Sensitized

persons may experience rapid irritation of skin upon exposure.

Persons with lung disorders or who are sensitized should not use this product.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO

Medical Conditions Generally Aggravated by Exposure

Allergy, skin disorders.

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

SKIN - PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists.

INHALATION - Move person to fresh air if effects occur. If needed, give oxygen or artificial respiration to improve breathing. Consult physician.

INGESTION - Get medical attention immediately. Never give liquids to an unconscious or convulsing person.

## SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type)

Provide adequate exhaust ventilation; use a NIOSH - approved respirator if PELS/TLVS are exceeded.

Ventilation	Local Exhaust	If needed.	Special	None known.
	Mechanical	Adequate exhaust ventilation must exhaust AWAY from applicator.		

Protective Gloves Natural rubber or Neoprene. Eye Protection Splash goggles or face shield.

Other Protective Clothing or Equipment

Use rubber apron, face shield and appropriate clothing to prevent contact with skin. Launder contaminated clothing before reuse. Discard contaminated leather shoes and canvas sneakers. Protective skin creams help cleaning with soap and water, gloves must still be worn. An eye wash station or an adequate supply of clean water must be available at work area.

Work/Hygienic Practices Enforce careful handling to prevent splashing. Wash thoroughly after use.

## SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled

Wear protective equipment to prevent exposure. Stop spill and dike to prevent spreading. Cover spill with absorbent materials and collect into containers. Clean contaminated area with detergent and water or a steam cleaner for best results.

Waste Disposal Method

Dispose in accordance with Federal, State and Local requirements.

Precautions to be Taken in Handling and Storing

Keep containers tightly closed when not in use.

Other Precautions NONE KNOWN.

Prepared by Samet Dy - Urethane Chemist

**PLEASE** \*The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use.\*

### SECTION I - IDENTIFICATION

IDENTITY (As Used on Label) **Dur-A-Crete Aggregate**

COMMON NAME Natural Aggregates Blend

#### HAZARD RATING

0 = Least  
1 = Slight  
2 = Moderate  
3 = High  
4 = Extreme

Health	3
Flammability	0
Reactivity	0
Personal Protection	F

### SECTION II - PRODUCT COMPONENTS

CAS.#	OSHA PEL	ACGIH TLV
Crystalline Silica (Quartz) <sup>1</sup>	14808-60-7	<u>10mg/m<sup>3</sup></u> 0.1 mg/m <sup>3</sup>
		%SiO <sub>2</sub> +2

<sup>1</sup>Crystalline silica can be a lung injury and cancer hazard. Do not breathe dust. May cause delayed lung injury. Long term exposure can cause silicosis, a respiratory disease which can result in a delayed, disabling, and sometimes fatal lung injury. Crystalline silica inhaled from occupational sources can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure. A single exposure will not result in serious and adverse effects.

T.S.C.A. Status - O.K. on all above components.

**\*FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300\***

### SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	4,000F	Specific Gravity (H <sub>2</sub> O = 1)	>1
Vapor Pressure (mm Hg)	N/A	Melting Point	3,000F
Vapor Density (AIR = 1)	N/A	Evaporation rate (Butyl Acetate = 1)	N/A

Volatile Organic Compounds (VOC) = Zero grams/liter

Solubility in Water Insoluble

Appearance and Odor Natural Aggregate. No odor.

### SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	N/A	Flammable Limits	LEL	UEL
			N/A	N/A

Extinguishing Media N/A

Special Firefighting Procedures

N/A

Unusual Fire and Explosion Hazards

N/A

### SECTION V - REACTIVITY DATA

Stability	Unstable	Conditions to Avoid
	Stable	X NONE KNOWN

Incompatibility (Materials to Avoid) Hydrofluoric acid and powerful oxidizing agents.

Hazardous Decomposition or Byproducts NONE KNOWN

Hazardous Polymerization	May Occur	Conditions to Avoid
	Will Not Occur	X NONE KNOWN

## SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Yes	YES	YES

Signs and Symptoms of Exposure Shortness of breath and reduced pulmonary function.

Health Hazards (Acute and Chronic) Note: Persons with lung disorders or who are sensitized should not use this product.

ACUTE - No symptoms

CHRONIC - excessive inhalation of dust may result in respiratory disease such as silicosis, pulmonary fibrosis, etc. The IARC has evaluated in Vol. 42 (monographs) that there is "sufficient evidence for the carcinogenicity of crystalline silica dust to experimental animals" and "limited evidence" with respect to humans.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	Yes (Respirable Quartz)	Yes * Level 2A Grouping	No

Medical Conditions Generally Aggravated by Exposure  
Lung disorders and persons subject to eye irritation.

### Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

SKIN - PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists.

INHALATION - Move person to fresh area if effects occur. If needed, give oxygen or artificial respiration to improve breathing. Consult physician.

INGESTION - Expected to be slightly toxic by ingestion. If swallowed, induce vomiting immediately as directed by a physician.

Get medical attention immediately. Never give liquids to an unconscious or convulsing person.

OTHER HEALTH EFFECTS - Medical conditions which may be aggravated by exposure to this product include, conjunctivitis of the eye, dermatitis of the skin, asthma and respiratory diseases. Sensitization may occur by skin contact.

**\*\*NOTE\*\*** persons with lung disorders or who are sensitized should not use this product.

## SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type): Atmospheric levels should be maintained below the exposure limits listed in section II by using engineering controls. Provide adequate exhaust ventilation and/or NIOSH approved cartridge respirator.

Ventilation	Local Exhaust	If needed.	Special	None Known.
	Mechanical	Adequate exhaust ventilation must exhaust AWAY from applicator.		

Protective Gloves	Natural rubber or Neoprene.	Eye Protection	Splash goggles or face shield.
-------------------	-----------------------------	----------------	--------------------------------

### Other Protective Clothing or Equipment

Use adequate ventilation and dust collection. To minimize exposure, wear a respirator approved for silica dust when using, handling, storing or disposing of this product. Refer to the most recent standards of ANSI (Z88.2), OSHA (29 CFR 1910.134), MSHA (30 CFR Parts 56 and 57), and NIOSH Respirator Decision Logic. Maintain, clean and fit test respirators in accordance with OSHA regulations.

Work/Hygienic Practices Avoid creating and breathing dust.

## SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

### Steps to be Taken in Case Material is Released or Spilled

Do not breathe dust. Do not rely on your sight to determine if dust is in the air. Silica may be in the air without a visible dust cloud. Avoid creation of respirable dust

### Waste Disposal Method:

Dispose in accordance with Federal, State and Local requirements.

Avoid creation of respirable dust. Take precaution against bag breakage

Other Precautions NONE KNOWN.

Prepared By: Samet Dy -Chemist

**PLEASE NOTE** "The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."